

Track-Safe™

Head of Wall Fire Protection

Installs on one side only,
protects Head of Wall at
concrete & fluted decks
in accordance
to UL 2079.

**TWICE THE PERFORMANCE
HALF THE LABOR**

- **One Size - One Side - All Applications**
- **Single Sided Installation**
- **Friction Fit, No Fastening Required**
- **Provides Fire & Smoke Protection During Vertical & Lateral Drift Movement up to 100%**
- **Approved for Shaft Walls**
- **No Fatigue & Maintenance Free**
- **Unlimited Shelf Life**



Track-Safe™

Head of Wall Fire Protection

ONE Product, ZERO Limitations

Flat Concrete Deck



For flat concrete deck, install header track to concrete deck as recommended by manufacturer. (A) Friction fit Track-Safe™ to header track on one side of wall before or after stud installation, no mechanical fastening required. (B) Install wall sheathing over Track-Safe™ to complete wall assembly.



Fluted Deck



For fluted deck, install header track to fluted deck as recommended by manufacturer. Friction fit Track-Safe™ to header track on one side of wall before or after stud installation, no mechanical fastening required. (C) On one side of wall assembly spray approved RectorSeal sealant over mineral wool and track safe as required by UL system. (D) Install wall sheathing over Track-Safe™ to complete wall assembly.



Contact: RectorSeal®

2601 Spenwick Drive, Houston, TX 77055

T 713-263-8001 | 800-231-3345

F 713-263-7577 | 800-441-0051

W www.rectorseal.com

C-G-13

Lifetime Warranty
Tested to UL 2079
STC Rating 57
L Rating > 1 CFM



Scan for
systems

